

# evo<sup>2</sup>



**CONSTANT EXTRACTION** Separated steam boiler and brewing group with our patented multi boiler technology. Set temperature with 0,1 degree precision and find your sweet spot.

**USABILITY** 54 mm-diameter portafilter, ergonomic handgrips, easy and quick milk frothing. Possibility to use the machine with dc system modules (GCS, MCS, OCS).

**ENERGY SAVING** Independent group give the possibility to turn off unused brewing groups or the boiler. All the material of evo2 guarantee the perfect thermal stability.

**SUSTAINABILITY** Lead Free: all parts exposed to water are in lead-free alloy (CW510L), certified by NSF. Construction materials are totally recyclable.

**BLACKBOARD EDITION** Make it your own. Customize your machine and add a personal touch on it. Let's play, write, erase and keep on creating.



## 3 GROUPS

|                                     |                    |
|-------------------------------------|--------------------|
| dimensions high version (w x h x d) | 940 x 525 x 525 mm |
| weight                              | 83 kg              |
| power consumption (24h-stand-by)    | 11,3 kW            |
| max power                           | 5,1 kW             |
| connected load                      | 220 V, 1 PH, 60 Hz |
| boiler capacity                     | 13 l               |
| capacity of group heads             | 0,5 l              |



### ARCTIC WHITE

3 gr. high version



### SPARKLING RED

3 gr. high version



### NEBULA BLACK

3 gr. high version



### QUARTZ GREY

3 gr. high version

**GCS** Grinder Control System - connection with dc one or dc two grinder  
**MCS** Milk Control System - requires a specific steam wand  
**OCS** Online Control system - remote control with LAN module and connection cable